

Telehandler / Zoom Boom

Used Telehandler San Francisco - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. This industrial equipment is commonly used in a variety of industries including agriculture. It is similar to a forklift and a crane as it has a boom, enabling it to extend upwards and forwards from the vehicle. The operator can utilize a variety of attachments at the end of the articulating boom to complete different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The pallet forks are the most popular telehandler attachment. These attachments help the operator transport different sized loads to many locations that would be considered unreachable with a traditional forklift. Telehandlers allow cargo pallets to be loaded and unloaded from a trailer and placed on high locations such as racking or rooftops. Normally, high rooftop applications would require the use of a crane; however, telehandlers can complete this task more efficiently. It can be expensive and impractical to rely on a crane or expansive industrial equipment to finish particular tasks. Within agriculture, the bucket or bucket grab is among the most popular attachments. Transporting items from unreachable places that cannot use a backhoe loader or a wheeled loader is one of the main advantages of using a telehandler. Telehandlers can directly access trailer units with high sides, hoppers or applications that would typically need a conveyor or loading ramp. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler machines can work in conjunction with a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. However, the main advantage of the telehandler is additionally its' largest limitation. The boom raises or extends with heavy loads, acting as a lever. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. A 5000 lb. capacity telehandler could lift 400 lbs. safely while fully extended with a retracted boom in conjunction with a low boom angle. Raising the same piece of equipment 70 degrees could allow this machine with a five thousand pound lift capability and retracted boom to support up to ten thousand pounds. There is a load chart on these machines to determine which tasks can be safely executed by taking the weight, angle and boom height into account. There are sensors and computers available on newer models. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. The lifting capacity is enhanced by front stabilizers that maximize the lifting capacity from a stationary position. A mobile crane can also use a bucket is another option consisting of a stabilized rotary joint found between upper and lower frames. There are compact telehandler models that differ in boom design, size, reach and weight. Telehandlers that weigh 11,000 pounds or less fall into the compact category. Compact units have a two-stage boom compared to larger machines that feature three or four boom designs. A low pivot boom ensures better operator visibility for transporting loads on compact units. Compact models are skinnier and have thinner dimensions. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. There are many different applications this machine is suitable for working in. It may be used as a tool carrier or a pick and place machine. This machine is often used in locations that are cramped and tight. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. These machines can facilitate internal building access. Compact telehandlers are used in many applications including nurseries, erecting steel, multi-story construction, masonry, strip malls, garages and similar jobs. Agri-business and farming applications rely on telehandlers for a variety of jobs. Telehandlers can be found with two and four-wheel drive and crab steering capabilities. The unit can travel over longer ranges at higher

speeds with two-wheel drive, making it ideal for moving throughout job sites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering is responsible for the increased maneuverability, allowing the front and rear wheels to shift forty-five degrees to the right or left. Compact telehandlers have varying cab environments. On entry-level models, there is a rollover cage for added safety. Higher-end models are equipped with a fully enclosed cab, a heater, windshield wiper and defroster. Compact units feature spacious cab accommodations to keep operators totally comfortable. Additional options including satellite radio, air conditioning, armrests, cup holders, suspension seats and tilt steering are available. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. These attachments increase the functions the machine is capable of. Compact units are more commonly utilized for ground engaging jobs. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer options are made for compact telehandler designs and ultimate versatility.