

Boomlift / Manlift

Used Boom Lift San Francisco - The boom lift is one of the most popular kinds of aerial machinery. Commonly known as aerial work platforms, mobile elevating work platforms, cherry pickers, aerial devices and elevating work platforms, it was engineered to complete work at higher locations more efficient and easier. There are many places to find boom lifts at work including warehouses, contractors, various companies and in retail stores. Staying safe while working at high altitude is essential for daily success. There is a wide variety of boom lift models to choose from. Many models are capable of being operated by a single individual. This equipment became popular in the orchard industry to harvest fruit without having to climb a ladder and balance heavy baskets or pails. It can be difficult to secure a ladder on farmland or in orchard settings. Harvesting fruit is much safer and simpler with a boom lift compared to using a ladder. Gaining Access Over Obstacles Certain boom lifts are designed to move up and over items. This makes working over obstacles possible This equipment is used in numerous industries including installing telephone poles and lines, maintaining overhead cables and window cleaning applications due to their ability to reach items when it is not practical to situate the machine directly underneath the issue. With a variety of joints allowing the machine to bend over or under items, the articulated boom lift is helpful for numerous applications. To enable operators to access many places, these sections of the boom lift can move independently. Articulated booms feature a tight turning radius, making them ideal for hallways and narrow storage corridors. Dual-fuel models can work both inside and outside. Diesel versions are best suited outside and electric models are preferred for interior environments. Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. These machines are often seen servicing overhead wires and power lines. Certain models are outfitted with water cannons to be used in firefighting applications. Telescoping sections are available on certain models to extend reach to the maximum. Some articulating boom lift models have an extra jib to enable their platform to reach six feet further in any direction. These boom lifts go by the nickname of "spiders," since their legs can support the entire machine on steep or difficult terrain. Capable of fitting through doorways, interior articulating boom lifts are more compact and used commonly in storage, retail and warehousing applications. Electric models are preferred in interior situations due to the danger that carbon monoxide exhaust poses and how much quieter these models are. Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. Instead, they extend outwards and upwards with hydraulics that retract and extend. The operator who is situated in the platform has the controls to operate and extend the lift on their own. Certain larger and taller models feature a jib located close to the top similar to an articulating boom lift model. Some models of boom lifts can achieve a reach of more than 180 feet. These machines are built to be stable and reliable. Some are able to extend to their full height capacity in less than 60 seconds. Adjustable speed, along with varying weight range capacities from 500 to 1000 lbs. are available in dual-fuel and diesel options. With 4WD options and their capacity to travel through small spaces, boom lifts are used in a variety of industries. Telescopic booms are common in a variety of settings due to their ability to combine height and reach. Jib Certain boom lift models have a jib or an extension located between the platform and the end of the main boom. This enables extra reach and another articulation point or hinge for the platform to move side-to-side or up-and-down. Jibs are an option on many telescoping and articulating boom lifts. There is an articulation point available on certain models situated halfway between the platform and the wheels to allow the machine to reach over an obstacle and be lowered again if needed. Genie Articulating Boom Lifts A popular type of articulating boom lift manufactured on the market is the Genie Z-boom Model. This unit offers exceptional versatility for accessing difficult to reach locations with the capacity to lift up, over and out with precision. In 1985, the first Genie Z-30/20 articulating Z-boom was introduced; their up-and-over capacity make them instantly popular and this design continues today. Proper Safety Measures When

operating any type of industrial equipment, safety is first and foremost. It is essential that all potential safety hazards are known to anyone working within the area to maintain a safe atmosphere. Operating the equipment safely is vital for the operator and everyone in the vicinity. Before operating the machine, effective communication and essential safety gear need to be in place. Ensure there are no flammable or combustible items, open flame or lit cigarettes near the machine, engine fuels or battery gases. For the ultimate safety, it is important to have a visible, safely mounted and accessible fire extinguisher within the operators reach. Keep work surfaces and charging stations clean and free from clutter or tools that could puncture the tires or damage the machine or its components. Daily Maintenance It is important to conduct a visual inspection prior to operating and to consult the maintenance manual to ensure everything is up to date. Stabilizing the weight is accomplished supportive devices to lift and distribute the load. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. It is very dangerous to reuse single use fasteners and other components as they might fail if used beyond their recommendations. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Safety can be increased with proper lighting and adequate ventilation along workbenches and within workshops and garages. Typically the wide umbrella of maintenance is distinguished by subsections such as Commissioning and Programmed Maintenance Intervals, Annual Maintenance, and Quarterly Maintenance. Maintenance Inspection Report Key components of the boom lift are divided up to categorize the inspection process. Some of the maintenance categories for the boom lift include the Engine, Platform, Controls and Function, Turntable, Booms and Drive Chassis. Improperly conducting maintenance can lead to unsafe working conditions, damaged components, reduced performance and ultimately downtime. A large part of keeping the boom lift secure and operational is the maintenance inspection report that ensures the operator is safe and monitors the machine's performance and service. The term commissioning refers to a list of single maintenance procedures that need to be completed at 50- and 150-hour intervals to keep the machine optimally running. There is quarterly and annual maintenance protocol that is conducted once or many times during the year. Programmed maintenance procedures are completed based on machine operating hours or during "pre-delivery" preparation. Prior to operating your equipment, check your maintenance manual to make sure all of the fluid levels, oil changes, battery life and maintenance are up to date.